

ACETONE

Product code: MS40025

Date of issue: 16/11/10

Replaces: 01/10/09

FORMULA : $\text{CH}_3\text{COCH}_3 = \text{C}_3\text{H}_6\text{O}$

(CAS : 67-64-1 / EINECS : 200-662-2)

2-Propanone, Dimethyl ketone

APPEARANCE

Colourless, clear solvent with a typical smell.

CONCENTRATION

Acetone : min. 99,5 % wt.

PHYSICAL PROPERTIES

Density (D20/4) : 0,790 – 0,793 kg/l
Refractive index (20°C) : 1,358 – 1,360
Colour Pt-Co (ASTM D 1209) : max. 5
Flash point (CC) (ASTM D 56) : max. -18 °C
Distillation range (ASTM D 1078) : max. 1 °C (56,2 °C included)
Water miscibility : complete

CHEMICAL ANALYSIS

Water : max. 0,3 % wt.
Acidity (as Acetic acid) (ASTM D 1613) : max. 20 ppm
Non volatile matter (ASTM D 1353) : max. 20 ppm
Benzene : max. 2 ppm
Permanganate time (ASTM D 1363) : min. 90 min.

PACKING

Can be obtained in bulk, multiboxes (711 kg), 200 lt-drums (160 kg) and 30 lt-cans (21 kg).
Other packing is available on request.

SAFETY REGULATION

DRUG PRECURSORS (REGULATION 111/2005 EC)

The safety data sheet is available on request.

Information in this publication is believed to be accurate and is given in good faith, but it is for the customer to satisfy itself of the suitability for its own particular purpose.

No representation, warranty or guarantee is made as to its accuracy, reliability or completeness.

COMPANY INFORMATION DISTRIBUTOR		
name	BRENNTAG N.V.	BRENNTAG Nederland B.V.
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht
country	Belgium	The Netherlands
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944
fax number	+32 (0)56 77 57 11	+31 (0)78 65 44 919
website	www.brenntag.be	www.brenntag.nl
e-mail	info@brenntag.be	info@brenntag.nl
activities	Distribution and export of chemicals and raw materials	
VAT number	BE0405317567	NL001375945B01
recall procedure available	Yes	
emergency number (24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944
QUALITY SYSTEMS		
ISO 9001	Yes	Yes
ISO 14001	Yes	Yes
ISO 22000	-	Yes
FSSC 22000	-	Yes
GMP+ -feed	Yes	Yes
OHSAS18001	-	Yes
ESAD	Yes	Yes
other	-	AEO