

!
!
!

Semi gloss varnish alternative. Provides an enhancing UV protecting film, bonds well to teak and other oily wood. Camouflages colour differences in wood. Prevents discoloring and emphasizes the natural wood grain. Excellent water resistance, maximum durability, UV protection and longevity.

! ! !

Full UV resistant system on all interior and exterior woodwork above the water-line. Especially suited for use on teak. Also as quick drying grain filling coat prior to applying Epifanes Clear Gloss Varnish or Epifanes Woodfinish Gloss. Maintenance of one- and two-component varnishes regardless which brand.

!
!
!

0,894 kg/dm³

!

25 seconds DIN-cup 4 mm.

! ! !

42 +/- 2 vol. %

!! !

508 grams/liter

!!

750ml.

! !

! ! !
! ! ! !

! ! !

!!!!!!!

! ! !

!

! !

!

! 60-70 µm wet = 20-25 µm dry

!

!

the Use


! !

14 m² (150sq feet) per litre @ 25 µm dry filmthickness

!! !

shape

! !



!
!
!
!
!

	5 - 10 %	0-5%
	1.3 mm - 1.5 mm	
	2-3 Bar	
	16 - 20 sec.	

! !

!
!
!
!
!
!
!

1 hour	2 hours	5-6 hours

! !

! ! !!

!				5-6 hours		
!						
!	6					

! ! ! !

!

!

Seller makes no express warranties.

by law, buyer's